



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
COM1	MO	P0	P3	P4	TU	1B	1C	1D	WE	TH	2B	2C	2D	FR	☀	❄	3B	3C
COM2	T1	P1	P2	1A	1F	1G	1E	COL	2A	2F	2G	2E	3A	SA	SU	3F	3G	

PIN	19	20	21	22	23	24	25	26	27	28	29	30
COM1	3D	AM	FLTR	4D	4E	4F	4A	5E	5F	5A	COM1	
COM2	3E	PM	HOLD	5D	4C	4G	4B	5C	5G	5B		COM2



NOTES:

1. VIEWING ANGLE: 6:00 O' CLOCK
2. DISPLAY MODE: POSITIVE/REFLECTIVE/TN TYPE
3. DRIVING VOLTAGE: 2.7V, DUTY: 1/2, BIAS: 1/2
4. OPERATING TEMP. : 0° C TO 50° C
5. STORAGE TEMP. : -10° C TO 60° C
6. CONNECTOR: PIN TYPE

6																			
5																			
4																			
3																			
2	MODIFY LOGIC AND ICON	18/06-08	L. M. L	DESIGN BY	Q B	26/05-08													
1	MODIFY LOGIC	28/05-08	R. Y. Z	CHECKED BY															
VER.	MODIFY CONTENTS	DATE	DESIGN	APP	BY														

PART NO. GD-5360P

TOLERANCES UNLESS OTHERWISE STATED
X: ±0.20
XX: ±0.10
ANGLES ±1°

ALL DIMENSIONS IN MM
UNLESS OTHERWISE STATED
CUSTOMER: S-TEK

COMPOSE TYPE:
 NO X-STEP: - # MM
 ALUM Y-STEP: - # MM

APPLICATION:

Instrument Audio Equipment Watch/Clock
 Telephone Automobile Other
 Home Appliances Air-condition

SAMPLE: Yes No

SHEET 1 OF 1