

# 2786 Decade Resistance Boxes



## SPECIFICATIONS

### Available Models:

Model Number	Resistance Range
278610	0.1 to 111,111Ω (six decade dials)
278620	1 to 1,111,110Ω (six decade dials)

**Residual Resistance:** Less than 23mΩ.

**Power Rating:** 0.3W/step, within 3W for overall instrument.

**Maximum Allowable Input:** 0.5W/step, 5W for overall instrument.

**Maximum Circuit Voltage:** 250V.

**Operating Temperature Range:** 0 to 40°C (32 to 104°F).

**Storage Temperature Range:** -10 to 50°C (14 to 122°F).

**Humidity Range:** 25 to 85%, relative humidity.

**Insulation Resistance:** More than 500MΩ at 500V DC.

**Dielectric Strength:** 1,500V AC for one minute.

Models 278610 and 278620 six-dial decade resistance boxes allow quick and easy setting of a wide range of resistance. These resistance boxes are used in combination with voltage or current standards to adjust voltage or current, as dummy load resistances or as an arm of AC bridges.

### Accuracy and Temperature Coefficient (2786):

Step	Accuracy* <sup>1</sup>	Temperature Coefficient* <sup>2</sup>		Reference Data	
		$\alpha_{23}$ ( $\times 10^{-6}/^{\circ}\text{C}$ )	$\beta$ ( $\times 10^{-6}/^{\circ}\text{C}^2$ )	Current Rating	Max. Allowable Input Current* <sup>3</sup>
0.1Ω	±2	±250	-0.4 to -0.8	1.7A	2.2A
1Ω	±0.5	±100	-0.4 to -0.8	550mA	710mA
10Ω	±0.1	±20	-0.4 to -0.8	170mA	220mA
100Ω	±0.05	±10	-0.4 to -0.8	55mA	71mA
1kΩ	±0.05	±10	-0.4 to -0.8	17mA	22mA
10kΩ	±0.1	±50	±0.1	5.5mA	7.1mA (10kΩ to 30kΩ) 250V (40kΩ to 100kΩ)
100kΩ	±0.1	±50	±0.1	250V (200kΩ to 1MΩ) 1.7mA (100kΩ)	250V

#### Notes:

\*1. At standard reference conditions of 23±3°C ambient temperature, 45 to 75% humidity and less than 0.1W application.

\*2. The resistance value at t°C can be expressed by the following equation:

$$R_t = R_{23} [1 + \alpha_{23} (t - 23) + \beta (t - 23)^2]$$

Where,  $R_t$  : Resistance value at t°C.

$R_{23}$  : Resistance value at 23°C.

\*3. Within five minutes.

#### NOTICE

- Before using the product, read the instruction manual carefully to ensure proper and safe operation

# YOKOGAWA

YMI-KS-HMI-SE01

## YOKOGAWA METERS & INSTRUMENTS CORPORATION

Global Sales Dept. / Phone: +81-422-52-6237 Facsimile: +81-422-52-6462  
E-mail: tm@cs.jp.yokogawa.com

YOKOGAWA CORPORATION OF AMERICA  
YOKOGAWA EUROPE B.V.  
YOKOGAWA SHANGHAI TRADING CO., LTD.  
YOKOGAWA ELECTRIC KOREA CO., LTD.  
YOKOGAWA ENGINEERING ASIA PTE. LTD.  
YOKOGAWA INDIA LTD.  
YOKOGAWA ELECTRIC CIS LTD.  
YOKOGAWA AMERICA DO SUL LTDA.  
YOKOGAWA AUSTRALIA PTY. LTD.  
YOKOGAWA MIDDLE EAST & AFRICA B.S.C(c)

Phone: +1-770-253-7000 Facsimile: +1-770-254-0928  
Phone: +31-88-4641000 Facsimile: +31-88-4641111  
Phone: +86-21-6239-6363 Facsimile: +86-21-6880-4987  
Phone: +82-2-2628-3810 Facsimile: +82-2-2628-3899  
Phone: +65-6241-9933 Facsimile: +65-6241-2606  
Phone: +91-80-4158-6000 Facsimile: +91-80-2852-8656  
Phone: +7-495-737-7868 Facsimile: +7-495-737-7869  
Phone: +55-11-5681-2400 Facsimile: +55-11-5681-4434  
Phone: +61-2-8870-1100 Facsimile: +61-2-8870-1111  
Phone: +973-17-358100 Facsimile: +973-17-336100

Subject to Change without notice.  
Copyright © 2005, Yokogawa Electric Corporation  
Copyright © 2010, Yokogawa Meters & Instruments Corporation  
[Ed: 04/b]

Printed in Japan, 108(KP)

<http://tmi.yokogawa.com/>